

DAILY DRILLING REPORT

HUMPHREY "A" #9
UNIT WELL # 13-- HUMPHREY "A" #9 --

HUMPHREY "A" #9, Langlie-Mattix Fld, Lea Co, NM. OBJECTIVE: CO, drill deeper 20', stimulate & convert to WIW. AFE 9294 - Mobil Intr 100% - Est Cost \$8000.

8/25/69 3535 TD, 3499 PBD.

MIRU Jake Miller Well Serv cable tool rig, strung up 3" tools w/ 4" bit, CO 3485-99, 14' in 3 hrs, drld plug 3499-3510, then CO 3515 w/ sd pump, stuck sd pump, fishing for 3½" OD x 51' Midco sd pump past 14 hrs, top of fish @ 3464.

HUMPHREY "A" #9, 3535 TD.

8/26 Ran 3-7/8 OD socket to 3464, failed to catch fish, ran imp blk, showed top of SP laying over on side of hole, rerun 3-7/8 socket, caught fish, jarred 1 hr, jarred off fish, ran short catch Bowen overshot, caught fish, jarred 4 hrs, rec top 28' of SP, top of fish @ 3492, prep to fish plunger out of SP.

HUMPHREY "A" #9, 3535 TD.

8/27 Fishing past 24 hrs for 23' of SP & 2½ x 3' plunger, cont to fish, top of fish @ 3492.

HUMPHREY "A" #9, 3535 TD.

8/28 Fished & rec 2½ x 3' plunger from top of SP, ran spear, caught sd pump, jarred on SP/6 hrs, jarred slips off spear, prep to drill by sd pump, top of fish @ 3492.

HUMPHREY "A" #9, 3535 TD.

8/29 Ran 4" bit, dlg by bailer 3493-96/7 hrs, broke pin on bit, fished for bit at 3490/12 hrs w/ 3-7/8 socket, no rec, now running imp blk.

HUMPHREY "A" #9, 3535 TD.

8/30 Drlg 4" @ 3493, drlg by bit 3490-96 and sd pump top @ 3492, fish for 12 hrs for bit - no success.

8/31 Drlg @ 3498 w/ 4" bit, drlg by 3½ bailer.

9/1 No rpt.

9/2 3502 fish for 4" bit past 8 hrs, drlg & ream to 3498, bit backed off, fish & rec in 8 hrs, drlg to 3499, bit backed off, fish & rec 8 hrs, drlg to 3502/8 hrs, fish past 8 hrs for bit @ 3496.

HUMPHREY "A" #9, 3535 TD.

9/3 3502 ND, fished out 4" bit @ 3496/6 hrs, fishing for bit @ 3490/18 hrs.

HUMPHREY "A" #9, 3535 TD.

9/4 Fish for 4" bit @ 3490/10 hrs, no success, rel Jake Miller Well Serv Cable Tool rig 4:30 p.m. 9/3/69, prep to RU West Texas Well Serv pulling unit.

HUMPHREY "A" #9, 3535 TD.

9/5 RU West Texas Well Serv DD unit, ran 3-7/8 OS w/ 3-1/16 grapple, 2-7/8 BS & jars on 2-3/8 tbg, OS stopped @ 3510, POH, no rec, ran 3-7/8 bit, 10 - 3" DC, stopped @ 3500, POH, ran OS, stopped @ 3500, POH, no rec, prep to run imp blk.

HUMPHREY "A" #9, 3535 TD.

WO CL tbg.