

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water injection well		7. Unit Agreement Name Stuart Langlie Mattix Unit
2. Name of Operator Gulf Oil Corporation		8. Farm or Lease Name
3. Address of Operator P. O. Box 980, Kermit, Texas		9. Well No. 128
4. Location of Well UNIT LETTER I , 1420 FEET FROM THE South LINE AND 100 FEET FROM THE East LINE, SECTION 10 TOWNSHIP 25S RANGE 37E NMPM.		10. Field and Pool, or Wildcat Langlie Mattix
15. Elevation (Show whether DF, RT, GR, etc.) 3124' KB		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER Surface string <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 11" hole 11-12-68. Reached TD of 1325' 11-14-68.
Ran 41 jts of 8-5/8" OD 24# J-55 casing and set at 1324'.
Cemented w/450 sx of Incor 4% gel, 2% CaCl₂, 1/4# Flocele
tailed w/100 sx Incor neat w/2% CaCl₂, 1/4# Flocele. Circulated
24 sx. Bumped plug w/1000#, float held. WOC 19-1/2 hrs.
Tested casing to 1000# for 30 minutes - O.K. Drilled cement
and float w/7-7/8" hole 11-15-68.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. F. Swannack TITLE Area Production Manager DATE November 18, 1968

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: