

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instruction 1 re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.  
LC-032579-C

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Justice-Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

23-25S-37E

12. COUNTY OR PARISH

Lea

13. STATE

NM

1. OIL ☒ GAS ☐ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR

King Resources Company

3. ADDRESS OF OPERATOR

300 Wall Towers West, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660 FSL &amp; 1980' FEL, Sec. 23, T-25-S, R-37-E Unit 0

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3191 GR. approx.

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☒

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

1. Set cement plug at 7180-7080 (35 sx cement)
2. Set cement plug at 6300-6200' (35 sx cement)
3. Run 5-1/2" csg., set at 6130' w/2 stage cement tool at 3650'.
4. Cement 1st stage with 350 sx Class "C" cement, w/cement circulated to bottom of San Andres at approx. 4600'.
5. Second stage cemented w/300 sx Trinity Lite cement & circulated back to the base of the salt.

1-8-69 Verbal Approval - Art Brown USGS Hobb, New Mexico

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Analyst

DATE 1-29-69

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 6 1969

\*See Instructions on Reverse Side

J L GORDON  
ACTING DISTRICT ENGINEER