

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

HOBBS
MAY 7 12 16 PM '69
Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-66

5a. Indicate type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name Langlie Mattix Woolworth Unit
8. Name of Lease Name
9. Well No. 105
10. Field and Pool, or Wildcat Langlie Mattix
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Injection - Drilling
2. Name of Operator Amerada Petroleum Corporation
3. Address of Operator Box 668, Hobbs, New Mexico
4. Location of Well UNIT LETTER P , 1690 FEET FROM THE North LINE AND 2020 FEET FROM West THE 28 LINE, SECTION 24-S TOWNSHIP 37-E RANGE 37-E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3247' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 6-3/4" hole to 3710'. Ran 4-1/2" OD 9.5# K-55 Casing with guide shoes on bottom and float collar at 3678', set at 3709' with 50 sx of lite wate cement and 300 sacks of Class H Cement W/5# salt per sack and 3/4 of 1% D-31. Pumped plug to 3679' at 7 AM 4-22-69. 21-1/2 hrs WOC. Tested casing W/1000# Helt OK. Top cement outside 4 1/2" Casing at 2700'.

hereby certify that the information above is true and complete to the best of my knowledge and belief.

[Signature] TITLE **Dist. Supt.** DATE **5-3-69**
BY [Signature] TITLE **Geologist** DATE **5-3-69**
ONS OF APPROVAL, IF ANY: