

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

APR 18 11 50 AM '69

<p><b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>4a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p>
<p>1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Injection</b></p>		<p>5. State Oil &amp; Gas Lease No.</p>
<p>2. Name of Operator <b>Amerada Petroleum Corporation</b></p>		<p>7. Unit Agreement Name <b>Langlie Mattix Woolworth Unit</b></p>
<p>3. Address of Operator <b>P. O. Box 668 - Hobbs, New Mexico 88240</b></p>		<p>8. Farm or Lease Name</p>
<p>4. Location of Well UNIT LETTER <b>F</b>, <b>1690</b> FEET FROM THE <b>North</b> LINE AND <b>2020</b> FEET FROM THE <b>West</b> LINE, SECTION <b>28</b> TOWNSHIP <b>24S</b> RANGE <b>37E</b> NMPM.</p>		<p>9. Well No. <b>105</b></p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) <b>Unknown</b></p>		<p>10. Field and Pool, or Wildcat <b>Langlie Mattix</b></p>
<p>12. County <b>Lea</b></p>		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 746'. Ran 24 joints 7-5/8" OD 24# H-40 casing with guide shoe set at 742'. Cemented with 400 sacks Class "C" cement with 2% calcium chloride. Pump plug to 712' at 2:15 p.m. 4-14-69. Cement circulated. 18 hours WOC. Tested casing with 1000# for 1/2 hour, held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Lo Stubb* TITLE District Superintendent DATE April 17, 1969

APPROVED BY *[Signature]* TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: