Form 9-331 (May 1963)	DEPARTM	JNITED STATES	; NTERIOR	SUBMIT IN TRIPLICA (Other instructions on verse side)	TE*	Budg		No. 42-R1424.	:
GEOLOGICAL SURVEY						LC	067968	4 2 3	
CUNDOW MOTICES AND DEPONTS ON WELLS								TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)						. 5.			
1. ;			<del></del>		7. UN	IT AGREE	MENT NAME	_ <u>≤ 5</u>	
OIL GAS WELL OTHER DTY								9,242	
2. NAME OF OPERATOR 8.							CASE NAME	7 4 . E	•
Cayman Corporation							ederal		
3. ADDRESS OF OPERATOR 9.							=		
512 Midland Savings Bldg., Midland, Texas 79701								用盘罩:	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* 10							POOL, OR W	ILDCAT	
See also space 17 below.) At surface							GNATED	要表示	
l <del></del>							M., OR BLK.	, AND	-
710 131 & 000 111						SURVEY	OR AREA	5748	
					٩	ec 3	ο π-24	-s', R-38	-E
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)							R PARISH 1		
3146'					т.	ea	i i	ew Mexic	·O
		·						<u> </u>	.~
16.	Check Ap	propriate Box To Inc	licate Natur	e of Notice, Report, (	or Other l	Data 🚆	Fig. (Fig.	T 3.3 5	
	NOTICE OF INTENT	NON TO:	1	SUE	SEQUENT RE	PORT OF			
		Г	—			0.1			
TEST WATER SHUT	i——	ULL OR ALTER CASING	-	WATER SHUT-OFF		٠	AIRING WEL		
FRACTURE TREAT	<u>  </u> ,	ULTIPLE COMPLETE		FRACTURE TREATMENT	- 3	* .	ERING CASI	"G	
SHOOT OR ACIDIZE	*	BANDON*	_	SHOOTING OR ACIDIZING	ا ≥لــا	_ AB/	NDONMENT*		
REPAIR WELL	c	HANGE PLANS		(Other) (Note: Report re	ults of mu	tiple cor	pletion on	Well	
(Other)		<u></u>		Completion or Rec	ompletion R	eport an	d Log form.	)	-
17. DESCRIBE PROPOSED proposed work, nent to this work	If well is direction	nally drilled, give subsu	face locations	ails, and give pertinent d and measured and true ve	ertical dept	ns for all	markers ar	zones perti	
2 17 70 6		a management 300	00 00! 5-	1/2" casing and	1737 6	 		sing.	••
2-17-70 Si	iot into and	i recovered 30:	99.33 3-	1/2 Casing and	1/3/.0		3/0 Ca	5411g.	
Placed cement plugs as follows:					i.	u nā.	1 T		
Ρ.	raced Cemen	_ prugs as ror.	.Ows.			123	il in the second		
		,	:01	a 20001					
			0 sacks			트림문화	72		
			75 sacks			104	rich S	글 분부가 그	
			'5 sacks			\$ 1.F			
2-23-70		•	25 Sacks	@ surface			• "	e 5. <del>12</del>	
_						-4			
II	installed marker.								
9.1-lb. per gallon weight mud used between cement plug								41	
						1.01			
							1 7 7 5		
ŧ						grafi	학교 통화		
, r									
18. I hereby certify th	at the foregoing is	true and correct				1 - 1	T		-
SIGNED	Mond	cicle m	LE	Engineer	<del></del>	DATE _	March	6, 1970	-
(This space for Fe	ederal or State offic	ee use)		APPR	OVEC	) — —		14 - <del>1</del>	=
			יד די			DATE			
APPROVED BY CONDITIONS OF	APPROVAL, IF A		LE	SEP 2	470				-