

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- W.I.W.	7. Unit Agreement Name
2. Name of Operator	Langlie-Mattix Queen Ut.
Mobil Oil Corporation	8. Farm or Lease Name
3. Address of Operator	9. Well No.
P. O. Box 633, Midland, Texas 79701	14
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>D</u> , <u>870</u> FEET FROM THE <u>North</u> LINE AND <u>1270</u> FEET FROM	Langlie-Mattix
THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>25-S</u> RANGE <u>37-E</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3114 GR	Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

LANGLIE-MATTIX 3/25/70

(8) 3480 TD, 1m, 7-7/8" hole, WOC, 4-1/2" csg, finish hole @ 7:00 a.m. 3/24/70, circ 1 hr, POH, Welex ran GR-N-Caliper logs 0-3467/5 hrs, ran bit to bottom, circ 1 hr, P & LD DP & DC's, ran 4-1/2 & 4-3/4 csg. to 3480, bottom up, guide shoe 3480, FC @ 3477, 1 jt. 4-1/2 9.50# csg. 3477 - 3448, 48 jts 4-3/4 16.0# J-55 LT&C csg 3448 - 1935, 60 jts 4-1/2 9.50# J-55 ST&C csg. 1935 - 0, Howco cemented csg on bottom w/ 750 x Class C cement 8% gel containing 3# gelsonite + 1/4# flocele/x + 150x Class C Neat, PD @ 1:15 a.m. 3/25/70, cement did not circ, WOC 4 hrs, Worth Well ran temp survey top of cement @ 310, WOC 18 hrs, test casing 1000# 30 min. OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Authorized Agent</u>	DATE <u>4-1-70</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u>4-1-70</u>
CONDITIONS OF APPROVAL, IF ANY:		