

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

**RECEIVED**

MAR 23 1970

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
9. State Oil & Gas Lease No.		

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. HOBBBS, N. M.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>WIW</b>	7. Unit Agreement Name <b>Langlie-Mattix Queen Unit</b>
2. Name of Operator <b>Mobil Oil Corporation</b>	8. Farm or Lease Name
3. Address of Operator <b>P.O. Box 633, Midland, Texas 79701</b>	9. Well No. <b>14</b>
4. Location of Well UNIT LETTER <b>D</b> <b>870</b> FEET FROM THE <b>North</b> LINE AND <b>1,270</b> FEET FROM THE <b>West</b> LINE, SECTION <b>14</b> TOWNSHIP <b>25-S</b> RANGE <b>37-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Langlie-Mattix</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3,114 GR</b>	12. County <b>Lea</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOB ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**LANGLIE-MATTIX QUEEN UNIT #14 WIW**

3/18 (1) 700 drlg sd & red bed, 12-1/4" hole. S. Mud.  
1/4 @ 216, 3/4 @ 510. C. A. Nunn Drlg Co spud in @ 2:00 P.M.  
3/17/70.

3/19 (2) 1056 ND anhy, WOC 8-5/8" csg., 1" @ 812; 1-1/2 @ 1056.  
Ran 31 jts. 1056 8-5/8 20# MU-46 8rd ST&C csg., cemented on  
bottom by Howco w/500x Class H 8% gel + 200x Class H Neat  
cement, all cement contained 1/4# flocele + 2% CaCl PD @  
8:15 P.M. 3/18/70, cement circ, WOC 18 Hrs. test csg. 1000# 30 min. ok,  
prep to drill 7-7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	TITLE <b>Authorized Agent</b>	DATE <b>3-20-70</b>
APPROVED BY	TITLE <b>SUPERVISOR</b>	DATE <b>3-23-1970</b>
CONDITIONS OF APPROVAL, IF ANY:		