

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP. TE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-068847

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME VACA DRAW
2. NAME OF OPERATOR American Quasar Petroleum Co. of New Mexico		8. FARM OR LEASE NAME VACA DRAW UNIT
3. ADDRESS OF OPERATOR 606 Vaughn Building/Midland Texas 79701		9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 660' FEL of Section 21, T-25-S, R-33-E (XXXXXXXXXXXXXXXXXXXX)		10. FIELD AND POOL, OR WILDCAT Undesignated
14. PERMIT NO.		11. SEC., T., R., OR B.L. AND SURVEY OR AREA Sec. 21, T-25-S, R-33-E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3392-KB		12. COUNTY OR PARISH Lee
		13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud Date: October 2, 1971 - 17 1/4" hole.

**10-3-71: Set 30" O.D. conductor casing 30' below ground level.
Cemented to surface with ready mix concrete.**

**10-10-71: Ran 23 joints 20" O.D. 94# per ft. H-40 8 round thread ST&C
Set 20" casing @ 920'. Cemented with 1250 sx. Howco Light cement
with 1/4# per sx. Floccel followed by 300 sx. Class-C cement with 2%
C.A.C.L.**

**10-23-71: Ran 120 joints 13 5/8" O.D. casing. Set @ 4986'. Cemented
with 2900 sx. Trinity Light Wt. cement and 300 sx. Class Neat cement.**

Circulated cement to surface on above casing strings.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jed Collins Jr

TITLE

President

DATE

11-16-71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DEC 20 1971

**U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO**

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

647-485

RECEIVED

DEC 14 1971

OIL CONSERVATION COMM.
HOUSTON, TEX.