

WRS COMPLETION REPORT

COMPLETIONS SEC 31 TWP 24S RGE 38E
PI# 30-T-0026 08/18/86 30-025-24035-0001 PAGE 1

NMEX LEA * 1980FNL 990FEL SEC SE NE
STATE COUNTY FOOTAGE SPOT
TEXACO PROD D X DO
OPERATOR WEST DOLLARHIDE (DRINKARD) UNIT
91 LEASE NAME
WELL NO. 3146DF DOLLARHIDE
OPER ELEV FIELD POOL AREA

API 30-025-24035-0001
LEASE TYPE NO. PERMIT OR WELL I.D. NO.
05/07/1986 07/01/1986 OIL-WO
SPUD DATE COMF. DATE TYPE TOO. STATUS

6800 DRINKARD NOT RPTD
PRO. DEPTH PRO. FORM CONTRACTOR
DTD 10275 PB 6800 OTD 10275 FM/TD ELLNBRGR
DRILLERS T.D. LOG T.D. PLUG BACK TO OLD T.D. FORM T.D.

LOCATION DESCRIPTION

6 MI NE JAL, NM

TUBING DATA

TBG 2 3/8 AT 6787

INITIAL POTENTIAL

IPP 50BOPD 31.0MCFD 306BW 24HRS
DRINKARD PERF W/ 228/IT 6387- 6692 GROSS 001
PERF 6387- 6393 6405- 6407 6417- 6421 6430- 6440
PERF 6450- 6456 6463- 6466 6473- 6475 6546- 6565
PERF 6583- 6596 6601- 6610 6621- 6625 6639- 6643
PERF 6650- 6654 6661- 6663 6667- 6674 6678- 6692
ACID 6546- 6692 17500GALS
15% NEFE
ACID 6387- 6475 8000GALS
15% NEFE
GTY 40.6 GOR 620

DRILLING PROGRESS DETAILS

TEXACO PROD
BOX 728
HOBBS, NM 88240
505-393-7191
OWWO: OLD INFO: FORMERLY HNG OIL 3 ELLIOT "31"
FEDERAL. ELEV 3146 DF. SPUD 2/7/72. 13 3/8 @
607 W/950 SX, 9 5/8 @ 3805 W/1450 SX, 7 @ 8985

CONTINUED IC# 300257000786

Copyrighted
Reproduction
Prohibited



Petroleum Information
CORPORATION

PI-WRS-GF
Form No 187

COMPLETIONS SEC 31 TWP 24S RGE 38E
PI# 30-I-0026 08/18/86 30-025-24035-0001 PAGE 2

TEXACO PROD D X DO
91 WEST DOLLARHIDE (DRINKARD) UNIT

DRILLING PROGRESS DETAILS

W/800 SX, 4 1/2 LNR @ 3500-8500 W/475 SX. LOG
TOPS: FUSSELMAN 8606, MONTOYA 8870, SIMPSON
9341. OTD 10275. PB 8985. COMP 5/7/72. IPP 154
BO, 10 BWP. PROD ZONE: FUSSELMAN 8587-8714.
01/08 LOC/1986/
08/06 DO CMT PLUGS TO 6800
08/11 10275 TD, PB 6800
COMP 7/1/86, IPP 50 BO, 31 MCFCG, 306 BWP,
GOR 620, GTY 40.6
PROD ZONE - DRINKARD 6387-6692

COUNTY LEA FIELD Dollarhide STATE NM
 OPR HNG OIL CO. API 30-025-24035
 NO. 3 LEASE Elliott "31" Federal SERIAL OWWO
Sec 31, T-24-S, R-38-E MAP
1980' FNL, 990' FEL of Sec CO-ORD

SPD CSG	Re- 3-6-73 CMP	CLASS		ELEV.		L & S	
		FORMATION	DATUM	FORMATION	DATUM		
	13 3/8" at 607' w/950 sx						
	9 5/8" at 3805' w/1450 sx						
	7" at 8985' w/800 sx						
	4 1/2" lnr 3500-8500' w/475 SX						
		TD 10,275'		PBD 7997'			

IP (Devonian) Perfs 7520-30' F 198 BOPD + 3 BW. Pot based
 on 24 hr test thru 1/2" chk. GOR 641; Grav 35.8; CP Pkr;
 TP 120#

CONTR OPRS ELEV 3146' DF PD 7997' TYPE WO

F.R.C. 4-7-73
 (Devonian)
 (Orig. comp 5-7-72 from (Fusselman) Perfs 8587-8714',
 OTD 10,275', OPB 8985')
 4-2-73 TD 10,275'; PBD 7997'; COMPLETE
 PB to 7997'
 Perf 7520-30' w/2 SPF
 Acid (7520-30') 1500 gals
 4-7-73 COMPLETION REPORTED

COUNTY **LEA** FIELD **Dollarhide** STATE NM **30-025-24035**
 OPR **HNG OIL CO.** MAP
3 Elliott "31" Federal
 Sec 31, T-24-S, R-38-E CO-ORD
 1980' FNL, 990' FEL of Sec
 Spd 2-7-72 CLASS
 Cmp 5-7-72 EL **31462**

	FORMATION		DATUM	
	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
13 3/8" at 607' w/950 sx				
9 5/8" at 3805' w/1450 sx				
7" at 8985' w/800 sx				
4 1/2" lnr 3500-8500' w/475 sx				
LOGS EL GR RA IND HC A				
	TD 10,275'; PBD 8985'			

IP (Fusselman) Perfs 8587-8714' P 154 BOPD + 10 BW. Pot based
 on 24 hr test. GOR 558; Grav 41.6

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. **Capitan** PROP DEPTH **10,500'** TYPE **RT**
 DATE

F.R. 2-8-72; Opr's Elev. 3124' GL
 PD 10,500' RT (Ellenburger)
 Contractor - Capitan
 5-27-72 AMEND FIELD NAME: Formerly reported as
 Undesignated.
 2-7-72 Drlg. 260' redbed
 2-15-72 Drlg. 3730' 1m
 2-12-72 Drlg. 5213' 1m
 2-28-72 TD 7690' 1m & sh; Prep DST
 DST 7177-7350', open 1 hr 15 mins, GTS 9 mins,
 rec 670' OCDF + 300' oil, 45 min ISIP 2311#,
 FP 234-304#, 2 hr FSIP 2937#, HP 3193-3216#
 3-6-72 Drlg. 9538' sh
 DST 7531-7690', open 2 hrs 15 mins, GTS 44 mins,

LEA
HNG OIL CO.

Dollarhide NM Sec 31, T24S, R38E
3 Elliott "31" Federal Page #2

3-6-72 Continued
Rec 90' oil + 300' GCDF, 45 min ISIP 703#,
FP 141-445#, 2 hr FSIP 1846#, HP 3332-3332#
3-14-72 TD 10,275'; Rng 7" Casing
3-21-72 TD 10,275'; PBD 8985'; Prep TO Pmp
Perf 8587-90', 8621-24', 8711-14' w/1 SPF
Acid (8587-8714') 6000 gals
Flwd 12 BFPH (90% oil + 10% wtr), TP 100#
3-28-72 TD 10,275'; PBD 8985'; RU Pmp
4-3-72 TD 10,275'; PBD 8985'; WO Potential
Ppd 225 BO + 5 BW in 24 hrs, GOR 760,
Grav 42.1
4-24-72 TD 10,275'; PBD 8985'; WO Potential

5-8-72 TD 10,275'; PBD 8985'; WO Potential
Ppd 154 BO + 10 BW in 24 hrs (8587-8714')
5-22-72 TD 10,275'; PBD 8985'; COMPLETE
7" Casing Collapsed
Ran 4 1/2" Patch Liner
LOG TOPS: Yates 2675', Queen 3565', San
Andres 3950', Tubb 5918', Abo 6550', Woodford
7390', Devonian 7511', Silurian 7700',
Fusselman 8606', Montoya 8870', Simpson 9341'
5-27-72 COMPLETION REPORTED