11

Form approved. Budget Bureau No. 42-R1424.

LEASE	DESIGNATION	AND	SERIAL	N

DEPARTMENT OF THE INTERIOR verse side?	5. LEASE DESIGNATION A	ND SERIAL NO.	
	LC - 069052		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
1. OIL X GAS WELL OTHER	7. UNIT AGREEMENT NAM	TE .	
2. NAME OF OPERATOR	8. FARM OR LEASE NAME	5	
HNG Oil Company	Elliott 31 F	ederal	
3. ADDRESS OF OPERATOR	9. WELL NO.		
P.O. Box 2267 Midland, TX 79702	7		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR	WILDCAT	
See also space 17 below.) At surface	Dollarhide Devonian		
1900' FNL & 2100' FWL, Sec. 31	11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA		
	Sec. 31, T24	S,R38E	
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE	
3093' GR	Lea	NM	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or O	ther Data		

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data


NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF: 5-21-82		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	BEPAIRING WELL ALTERING CASING ABANDONMENT*	
REPAIR WELL (Other)	<u></u>	CHANGE PLANS		(Other) (Note: Report results of mult Completion or Recompletion Re	iple completion on Well port and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) •

6-8-82 - Set Baker cement retainer at 7724' - Circ hole with 10 ppg gelled brine squeezed perfs. 7919-7924 + 7822-7827 with 50 sx C1 H; left 2 bbls cmt on top of retainer.

TOH to .3605' - mix 25 sx & spot cement plug from 3605-3505.

6-9-82 - Set 10 sx C1 H 30' to surface. Cut off casing, installed dry-hole maker. Well P&A 1:00 p.m.



SAQ SING YAYRUS IA GIQQIGGG GU OGIXAW WIZN GABU SOG

SIGNED SETTLY AND BETTY GILDON TITLE Regul.	atory Analyst DATE June 11, 1982
(This space for Federal of With Police Ver !)	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	DATE
NOV 2 1982	
FOR JAMES A. GILLHAM *See Instructions on DISTRICT SUPERVISOR	Reverse Side