HOBBS, NEW MEXI	
M-Roswell, 1-File, 1-Engr Jim, 1-Foreman CK, 1-J Form 9-331 Dec. 1973	A, 1-BB, 1-Mr. J.A. Midland, Form Approved. Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	LC = 0.32650 (b)
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	A.B. Coates C
well well other	9. WELL NO.
2. NAME OF OPERATOR	29
Getty Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Justis Ellenburger
P.O. Box 730, Hobbs, NM 88240	11. SEC., T., R., M., OR BLK. AND SURVEY O
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) /(.52 AT SURFACE: 1605 FNL & 330 FEL	Sec. 24, T-25S, R-37E
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Lea NM
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.
REPORT, OR OTHER DATA	15 ELEVATIONS (SHOW DE KED IND
	15. ELEVATIONS (SHOW DF, KDB, AND WD 3068' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	जाल मि
TEST WATER SHUT-OFF	C I OSW
SHOOT OR ACIDIZE	
	(NOTE: Report results of multiple completing or zon
PULL OR ALTER CASING MULTIPLE COMPLETE	change on Form 9=330.)
ABANDON*	
(other)	

.

17. Describe PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 11/21/83 Rig up, pull rods, pump and 2 7/8" & 2 3/8" tbg, tag bottom @ 7948'.

±±/ ±±/ 05	rig dp, puir rous, pump and 2 //8 & 2 3/8 tbg, tag bottom @ /948.
11/22/83	Ran 5 $1/2$ " csg scraper to 7948'. Ellenburger w/ 1 SPF @ 7526-33' =8 holes,
	7537-40' - 4 holes, 7544-55 = 12 holes, total of 24 holes.
11/25/83	Treat perfs @ 7526-7790' w/ 7500 gal 15% & 1500# rock salt in 3 stages, Max
	press 2100#, min press 200#. Flush w/ 43 bbls, ISIP 300#. vac. in 2 min.

	P1000	2100 #	, min br	255 2001	r. ritusi	1 W/ 45	DDIS,	TOTA	300#,	vac.	ın	Z min.
11/26/83	Ran 2	3/8" +	tubing.	Set @ 7	7818'.	Placed	well	on pro	oductio	on.		

	Subsurface Safety Valve: Manu. and Type		Set @	. Ft.
<i>A</i> fa	18. I hereby certify that the foregoing is true is signed SIGNED Dale R. Crockett	and correct	November_29, 1983	3
		is space for Federal or State office use)		
	MAY 8 1984			
	Carlsbad BOSTOBA, NEW MEXICO	*See Instructions on Reverse Side		