

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65.

NEW MEXICO OIL CONSERVATION COMMISSION

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-	7. Unit Agreement Name
2. Name of Operator UNION TEXAS PETROLEUM CORPORATION, A Division of Allied Chemical Corp.	8. Farm or Lease Name Crosby Deep
3. Address of Operator 1300 Wilco Building, Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER <u>G</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>25-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
11. Elevation (Show whether DF, RT, GR, etc.) 3015' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPERATIONS ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER <u>Production String</u> ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17½" hole @ 9 P.M., CST, November 15, 1972.

September 17, 1972, TD 512' set 13 3/8" 48#, H-40 csg. @ 504'. Cemented w/500 sx. Class "C" and circ. cement. WOC 24 hrs. Tested csg. w/1000 psi for 30 min. w/no dec. in pressure.

November 29, 1972, 12¼" hole, TD 3820', set 9 5/8", 36# K-55 @ 3812'. Cemented 1st Stage w/900 sx. of Lite-wate + 8% Gel, tailed in w/150 sx. of Class "C" w/1% CaCl₂. Plug down @ 7:18 A.M., CST, November 30, 1972. DV tool set @ 1814'. Cemented 2nd Stage w/1200 sx. of Lite-wate + 8% Gel, tailed in w/50 sx. Class "C" w/1% CaCl₂. Cement Circ. WOC 24 hrs. Pressured csg. to 1500 psi for 30 min. w/no dec. in pressure.

January 10, 1973 8 3/4" hole, TD 10,445' set 5½" 17# J-55 & N-80 @ 10,445'. Cemented 1st Stage w/350 sx. Class "H" 50/50 Lite-poz. FC @ 10,423' & DV tool @ 9317'. Cemented 2nd Stage w/540 sx. Dowell expanding cmt. Closed DV tool @ 11:25 P.M., CST. Top cement @ 7030'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert H. Plummer TITLE Operations Supt. Western Area DATE January 31, 1973

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE FEB 6 1973

CONDITIONS OF APPROVAL IF ANY: