

NO. OF COPIES RETURNED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☐ Fee ☒
1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- Dual Oil & Gas Well		7. Unit Agreement Name
2. Name of Operator UNION TEXAS PETROLEUM, A Division of Allied Chemical Corporation		8. Farm or Lease Name Crosby Deep
3. Address of Operator 1300 Wilco Building, Midland, Texas 79701		9. Well No. 2
4. Location of Well UNIT LETTER <u>G</u> <u>2310</u> FEET FROM THE <u>East</u> LINE AND <u>1650</u> FEET FROM THE <u>North</u> LINE, SECTION <u>33</u> TOWNSHIP <u>25-S</u> RANGE <u>37-E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3015' DF		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☒ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1701.

Spudded 17½" hole @ 9 P.M., CST, November 15, 1972.
 September 17, 1972, T.D. 512', set 13 3/8", 48#, H-40 @ 504'. Cemented w/500 sx. Class "C" and circulated cement. W.O.C. 24 hrs. Tested casing to 1000 psi for 30 min, w/no decline in pressure.

November 29, 1972, T.D. 3820', set 9 5/8", 36#, K-55 @ 3812'. Cemented 1st Stage w/900 sx. of Lite-wate + 8% Gel, tailed in w/150 sx. of Class "C" w/1% CaCl₂. Plug down @ 7:18 A.M., CST, 11-30-72. D.V. tool set @ 1814'. Cemented 2nd Stage w/1200 sx. of Lite-wate + 8% Gel. tailed in with 50 sx. of Class "C" w/1% CaCl₂. Closed D.V. tool @ 1:30 P.M., CST, 11-30-72. Cement circulated. W.O.C. 24 hrs. Pressured casing to 1500 psi w/no decline in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert F. Vernon TITLE Operations Supt. Western Area DATE December 6, 1972

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE DEC 8 1972

CONDITIONS OF APPROVAL, IF ANY: