Form 9-331 (May 1963)

UN' D STATES SUBMIT IN TRIPI OF THE INTERIOR (Other instructions verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

re-

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			LC 06796	LC 067968 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
			6. IF INDIAN, AL		
			7. UNIT AGREEM	ENT NAME	
OIL X GAS OTHER Plug & Abandon 2. NAME OF OPERATOR			P many on this	8. FARM OR LEASE NAME	
Atlantic Richfield Company 3. ADDRESS OF OPERATOR			9. WELL NO.	J. H. McClure "A" 9. WELL NO.	
P. O. Box 1710, Hobbs, New Mexico 88240			22		
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FNL & 1830' FEL (Unit letter G)				10. FIELD AND POOL, OR WILDCAT	
			West Dolla	rhide Dev.	
			11. SEC., T., R., I	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
			7		
				30-24S-38E	
. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)		12. COUNTY OR			
3169	9.40' DF		Lea	N.M	
6. Check Appropriate Box To In	dicate Natu	e of Notice, Report, o	r Other Data	,	
NOTICE OF INTENTION TO:	1	,	EQUENT REPORT OF:		
	——————————————————————————————————————			IRING WELL	
TEST WATER SHUT-OFF PULL OR ALTER CASING FRACTURE TREAT MULTIPLE COMPLETE		WATER SHUT-OFF FRACTURE TREATMENT		RING CASING	
FRACTURE TREAT SHOOT OR ACIDIZE ABANDON*		SHOOTING OR ACIDIZING		DONMENT*	
			ug & Abandon	· & Abandon X	
(Note: Report results			ults of multiple comp mpletion Report and	s of multiple completion on Well pletion Report and Log form.)	
On 4/21/75 rigged up & ran bit & csg w/5½" cmt retr on 2-3/8" tbg, set @	g scraper	to 7800'. POH v	w/bit & csg s	scraper. WIH	
sx Cl C, 4% gel, below retr. MP 300 up to 6000'. Spotted 40 sx Cl C 4% @ 4580'. POH w/99 jts 5½" 17# LTC Cl C Neat cmt 4440-4640' across 5½" across 8-5/8" csg shoe @ 3897'. Spotted 50 sk cmt plug @ surface. Insta 4/25/75. Final Report. Location to when well location is ready for final	gel, 570 csg, (rec csg shoe otted 125 alled reg o be clea	0-6000'. POH w/overed total of overed 40 sx sx Cl C Neat cm ulation dry hole ned & levelled.	cmt tool. Ct 4580'). Spot Cl C Neat cn t 750-1300'. marker. Wel	it 5½" OD csg tted 40 sx at 3700-3913' POH w/tbg. L1 P&A effectiv	
18. I hereby certify that the foregoing is true and correct					
	TLE Dis	t. Drlg. Supv.	DATE	4/30/75	
(This space for Federal or State office use)		The second secon			
APPROVED BYT	TLE	-00000	DATE/		
CONDITIONS OF APPROVAL, IF ANY:		\ D. P.		-	

*See Instructions on Reverse Side NOV A