			· Prillay	140.00
Form 9-331 (May 1963)	DEPARTN	re Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.		
	G	T OF THE	LC 067968	
				6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not	SUNDRY NOTI use this form for propos Use "APPLICA			
1.		7. UNIT AGREEMENT NAME		
WELL	WELL OTHER			
2. NAME OF OPE	RATOR	8. FARM OR LEASE NAME		
А	tlantic Rich	J. H. McClure "A"		
3. ADDRESS OF O		9. WELL NO.		
P	. O. Box 197	8, Roswell,	New Mexico 88201	22
4. LOCATION OF	VELL (Report location cl	10. FIELD AND POOL, OR WILDCAT		
See also space At surface	· 17 below.)	Undesignated-Dev.		
		.11. SEC., T., R., M., OR BLK. AND		
2310	' FNL & 1830	SURVEY OR AREA		
				Sec. 30, T24S, R38E
14. PERMIT NO.		15. ELEVATIONS (Show	whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
		3169	.40' DF	Lea N.M.
16.	C			
10.	Спеск Ар	propriate box to in	dicate Nature of Notice, Report, o	r Other Data
	NOTICE OF INTENT	TION TO:	SUBS	SEQUENT REPORT OF:
TEST WATER	SHUT-OFF P	ULL OR ALTER CASING	WATER SHUT-OFF	X REPAIRING WELL
FRACTURE TR	EAT M	ULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
		BANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	c	HANGE PLANS	(Other)	
(Other)		ults of multiple completion on Well empletion Report and Log form.)		
17. DESCRIBE PROF	POSED OR COMPLETED OPER	AATIONS (Clearly state a	Il pertinent details, and give pertinent da	tes, including estimated date of starting any
nent to this	work.) *	ianiy utmeu, give subsu	trace locations and measured and true ver	rtical depths for all markers and zones perti-
			:	
D	rilled 12날"	hole to 389	8'. Ran 32 jts 8-5/8	32# н cl. т = 5
	-		24# J Cl. I casing w/	· · · · · · · · · · · · · · · · · · ·
			'. Set @ 3897.37' RK	
			_	
			Class C cement contai	-
		•	flake & 200 sx Class	
C	irculated.	Circ 380 sx	to pit. Plug down @	1:30 PM [] [4]
1	2/1/72. WOC	22 hrs. T	ested 8-5/8" casing w	//1000# for 175
3	O min. Held	OK. Resum	ed drilling on format	ion @ 2:00 PM
			rld to T.D. 8016'. F	
-	-,-,,-,	D		TO THE STATE OF TH

casing & 195 jts 8-5/8" 24# J Cl. I casing w/float collar and float shoe = 3877.92'. Set @ 3897.37' RKB. Cemented 8-5/8" casing w/1300 sx Class C cement containing 2% Lo-Dense, 3#/sk salt, l½#/sk Celloflake & 200 sx Class C neat. Cement circulated. Circ 380 sx to pit. Plug down @ 1:30 PM 12/1/72. WOC 22 hrs. Tested 8-5/8" casing w/1000# for 30 min. Held OK. Resumed drilling on formation @ 2:00 PM 12/2/72, 7-7/8" hole. Drld to T.D. 8016'. Ran 250 jts 5½" 8R 17# J-55 LT&C Cl. II csg w/float collar & guide shoe & 6 centralizers = 7999.93', set @ 8016.13'. Cemented w/200 sx Class C cmt containing 4% gel & 300 sx Cl. C neat cement. Plug down @ 11:15 PM 12/15/72, w/1600#. WOC 72 hrs. Tested casing to 2000#, OK.

18. I hereby certify that the foregoing is true and correct SIGNED Autolog	Dist.	Drlg.	Supervisor 1/3/73	
(This space for Federal or State office use)				
,			물질하신 하 살림 이 유럽 하	

TITLE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

U. S. GEOLOGICAL SURVEY

HOBBS, NEW MEXICO

J. A. Carrier

2 5 2 3 6 1 3 2 3 5 5 5 5 6 6 7 5 6