

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions
verse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 034117 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR	9. WELL NO.
Greathouse & Lovelady Oil & Gas, Inc.	U. S. Crosby
P. O. Drawer 2666 - Midland, Texas 79701	1. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
660' FSL & 1980' FWL	Crosby-Davonian
14. PERMIT NO.	11. SEC., T., R., E., or B.L. AND SURVEY OR AREA
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	28-258-378
3007 Gr.	12. COUNTY OR PARISH
	13. STATE
	Lea New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Set retainer at 7974' and squeezed open hole section 8065-8160' with 300 sacks. ROH to 6750' and reversed out 20 sacks. Left cement in 5-1/2" casing from 6750' to total depth. Loaded 5-1/2" casing with 9.5# mud. 3/30/74
2. Cut 5-1/2" casing at 4635' and POH. Spotted 50 sacks cement at 4600', 50 sacks at 3650'. 4/3/74
3. Cut 8-5/8" casing at 2448' and POH. 4/3/74
4. RIH with tubing and spotted 65 sacks cement at 960'. Did not hold. Waited overnight and mixed mud and lost circulation material. Spotted second 65 sacks plug. Held O.K. 4/4/74
5. Spotted 65 sacks cement at 560' and 10 sacks at surface. Installed marker. 4/5/74
6. Labeled pits and location. Area ready for inspection.
7. All plugs checked by U.S.G.S. Engineer.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. T. Hansen

TITLE Production Superintendent

DATE

July 6, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED
ARTHUR R. BROWN
DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths, (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.