

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. <b>NM 7486</b>
2. NAME OF OPERATOR <b>CONTINENTAL OIL COMPANY</b>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <b>P. O. Box 460, Hobbs, N.M. 88240</b>		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <b>1980' FSL &amp; 1980' FEL of Sec. 29</b>		8. FARM OR LEASE NAME <b>Jack A-29</b>
14. PERMIT NO.		9. WELL NO. <b>8</b>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <b>3,266' GR (Est.)</b>		10. FIELD AND POOL, OR WILDCAT <b>Gulmet Yates Pool</b>
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <b>Sec. 29 T-24S R-37E</b>
		12. COUNTY OR PARISH <b>Lea</b>
		13. STATE <b>N. Mex.</b>

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Squadded 12 1/4" hole on 7-24-74, and drilled to 400'.  
Set 8 5/8" 20# casing at 400' and cemented with 260  
lb. Class "C" Cement. Circulated cement to  
surface. Tested casing with 1,000#, held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Alternate for  
Division Office Manager

DATE 7-30-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 1 1974

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side

USGS-5, NMFD-4, File