

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-11768

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "76"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Langlie-Mattix

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9-T25S-R37-E

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Morris R. Antweil

3. ADDRESS OF OPERATOR

Box 2010, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 330' FEL Sec. 9-T25S--R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3128' GR

12. COUNTY OR PARISH 13. STATE

Lea NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 13-3/8" conductor casing at 40' with rathole digger and cemented to surface. Spudded at 10:30 AM 26 Mar. 76. Drilled 12-1/4" hole to 810'. Cemented 9-5/8" 36# & 40# J-55 casing @ 810' with 450 sx. Class H cement containing 2% CaCl₂ and 1/4#/sx Flocele. Plug down at 4:30 PM 27 Mar. 76. Circulated out approximately 150 sx. cement. WOC 18 hrs. Tested casing with 1000 psi for 30-mins. with no loss in pressure. Drilled out with 7-7/8" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ed Williams

TITLE

Agent

DATE


31 March, 1976

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE



*See Instructions on Reverse Side