

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SAINT A FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-DRILL OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER-
2. Name of Operator
Doyle Hartman
3. Address of Operator
312 C & K Petroleum Bldg., Midland, Texas 79701
4. Location of Well
UNIT LETTER A 480 FEET FROM THE North LINE AND 660 FEET FROM
THE East LINE, SECTION 19 TOWNSHIP 24-S RANGE 37-E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.)
3292 GL

7. Unit Agreement Name
8. Farm or Lease Name
Cities Thomas
9. Well No.
2
10. Field and Pool, or Wildcat
Langlie Mattix
12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ CHARGE PLANS ☐ CASING TEST AND CEMENT JOBS ☒ OTHER ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled well to a total depth of 3711 feet. Logged well with CDL-Neutron-GR and Guard-FORXO logs. Ran 91 jts (3715 feet) of 4 1/2 inch OD, 10.5 lb/ft, J-55, EUE, 8 RD casing and landed at 3709 RKB. Cemented casing with 1300 sx of API Class-C cement containing 3% Halliburton Econolite followed by 250 sx of 50-50 POZ containing 18% salt. Plug down 4:53 PM CDT 4/30/77. Pressure tested casing to 1500 psi. Pressure held okay. Ran temp survey and found top of cement 900 feet from surface. Rigged up Halliburton and cemented down annulus at 2 BPM at 250 psi. After pumping a total of 300 sx of API Class-C cement, cement squeezed at a pressure of 500 psi. Cementing work completed 5/3/77.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Doyle Hartman TITLE Operator-Part Owner DATE 5/12/77
Orig. Signed by
Jerry Sexton
Dist. L. Supv.
APPROVED BY _____ TITLE _____ DATE MAY 16 1977
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 13 1977

**OIL CONSERVATION COMM.
HOBBS, N. M.**