COPY TO Q. C. C.

... Form Approved. Budget Bureau No. 42-R1424

UNITED STS
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) 1. oil	6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Carlson B-13 9. WELL NO. 8 10. FIELD OR WILDCAT NAME Justis - Tubb Drinkard		
1. oil gas well other 2. NAME OF OPERATOR Terra Resources. Inc.	8. FARM OR LEASE NAME Carlson B-13 9. WELL NO. 8 10. FIELD OR WILDCAT NAME		
1. oil gas well other 2. NAME OF OPERATOR Terra Resources. Inc.	8. FARM OR LEASE NAME Carlson B-13 9. WELL NO. 8 10. FIELD OR WILDCAT NAME		
well well other 2. NAME OF OPERATOR Terra Resources. Inc.	9. WELL NO. 8 10. FIELD OR WILDCAT NAME		
Terra Resources. Inc.	8 10. FIELD OR WILDCAT NAME		
Terra Resources, Inc. 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	•		
3800 Buffalo Spdwy., Ste. 300 Houston, Tx	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA _		
AT SURFACE: 990'FNL&FEL of Sec 13	Sec. 13 255 R37E N.M.P.M.		
AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE		
AT TOTAL DEPTH: Same	Lea New Mexico		
 CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 	14. API NO.		
METONY, ON OTHER DATA	15. ELEVATIONS (\$HOW DF, KDB, AND WD)		
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	(AND NO)		
ST WATER SHUT-OFF [7] Surface Casino	Setting		
WIOTONE TREAT	3 Secting		
HOOT OR ACIDIZE	- · · · · · · · · · · · · · · · · · · ·		
ULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone		
ULTIPLE COMPLETE	change on Form 9-330.)		
HANGE ZONES			
BANDON*			
	•		
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dis measured and true vertical depths for all markers and zones pertinent 	all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and		
and Johnson	to this work.)*		
Set 8 5/8" surface casing at 1149'. Cemen w/4% gel and 2% CaCl and 200 SX Class C w/	ted with 400 SX Class "C"		

w/4% gel and 2% CaCl and 200 SX Class C w/2% CaCl. Plug held at 700#. Cement circulated to surface w/full returns. Casing was 24#/ft. K-55 ST&C.

RECEIVED ... JIIN 26 1978

U. S. GEOLOGICAL SURVEY

		HOBB	S. NEW MEXI
Subsurface Safety Valve: Manu. and Type		Set @	
18. I hereby certify that the foregoing is true and correct			, , , , , , , , , , , , , , , , , , ,
SIGNED DIST.	Opr. Engr. DATE	6-23-78	
(This space for Federal	al or State office use)		
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	DATE		

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUN 26 1978

U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO