

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFG. NO.	NO. SUB.
a	double upset bolt s/sq. nut, round washer, and cotter key on short end, sq. nut and if locknut on long end, 15 1/8" long (or length required.) wet process porcelain secondary spool insulator, 3", brown glaze	7828	1101		
b	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-13 Note: provide clamp and ground conduit parallel groove clamp, size req'd			FLANDY SERIES UC	
c	secondary insulator clevis for 4" insulator 3/8" thimble nut	6510			
d	3/8" x 12" (or length req'd) straight thimble bolt w/sq. nut	5512			
e	transformer cluster mount bracket (small)			ALPHA FORM 6M3-6	X
f	transformer cluster mount bracket (large)			ALPHA FORM 15M3-6	X
g	req'd size raintight disconnect & fuse, 3-phase, 600 V. Ref. Dwg No. ES-14				
h	16" cross plate anchor (or size req'd)	X-16			
i	8-way expanding anchor (size req'd)	88135			
j	4" brown glaze wet process porcelain secondary spool insulator		10101		
k	3/8" x 7' thimble anchor rod w/nut (use twineye if req'd - Chance No. 5347)	5317 (NUT 55006P)			
l	3/8" high strength guy strand (10,800 lb.)				
m	preformed guy grip for 3/8" guy strand	5010			
n	3/8" x 10" angle thimble bolt w/nut	68-3 1/2			X
o	3" x 1/4" x 11/16" hole curved washer				
p	6" - guy clamp w/3-1/2" bolts				
q	medium size strain insulator				
r	serving sleeve for 3/8" guy strand	6454			
s	3/16" x 2-1/2" x 7" lift plate	7887			X
t	pole bottom ground plate (may use butt-wrap if desired)				
u	Ground Connection (See Dwg. ES-12)				
v	wet process porcelain secondary spool insulator, 3" - white glaze				
w	wet process porcelain secondary spool insulator, 4" - white glaze				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO PRODUCTION DEPT. HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPECS	DRAWING NO: ES-1 SHEET 3 OF 3

46115 B-1 No. 4

RECEIVED

MAY 10 1977

U.S. CONST. COMM.
HODGES, R. M.