

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SALE		
FILE		
J.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-2317	
7. Unit Agreement Name	
8. Farm or Lease Name M E. Hale State	
9. Well No. 2	
10. Field and Pool, or Wildcat Langlie Mattix	
12. County Lea	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>
Name of Operator Tahoe Oil & Cattle Co.		
Address of Operator P. O. Box 7032, Midland, Texas 79703		
Location of Well		
UNIT LETTER H	2255	FEET FROM THE North
LINE AND	860	FEET FROM
East	2	TOWNSHIP 25S
THE	37E	RANGE
N.M.P.M.		

15. Elevation (Show whether DF, RT, GR, etc.)  
3135.2 GL

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLAYS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded 4:00 P.M. January 8, 1978, Drilled 12-1/4" hole to 375'
- Ran 9 Jts. 8-5/8" 24# K-55 New Casing set at 372' G.L. Cemented (Halliburton) with 300 Sx. + 2% Calcium Chloride. Plug down 1:30 A.M. January 9, 1978. Cement Circulated to surface.
- W.O.C. 12 hrs. tested casing and B. O. P. equipment to 1000#.
- Drill out with 7-7/8" bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>K. A. Freeman</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>1/12/78</u>
Orig. Signed By Jerry Sexton Dist. L. Supv.		
PROVED BY	TITLE	DATE
ADDITIONAL APPROVAL IF ANY:		

JAN 16 1978

RECEIVED

JAN 13 1978

OIL CONSERVATION COMM.  
HOBBS, N. M.