

10/24/79

COPY TO O. G. A.

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other Dry
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FSL & 1980' FWL, Sec. 9
AT SURFACE: (Unit K, NE/4 SW/4)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input checked="" type="checkbox"/>
(other)			

5. LEASE
NM-14212
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Langlie C Federal
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Jalmat Yates Seven Rivers
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
9-25-37
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KD3, AND WD)
3149.8 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged and Abandoned well by spotting a 26 sx Class H cement plug 2950'-3150'. Spotted a 25 sx Class H cement plug 965'-1165'. Ran free point and cut and pulled 539' 5-1/2" casing. Spotted a 20 sx Class H cement surface plug. Weld on cap and erected P X A marker. Clean and level location. Will notify when location ready for final inspection.

PA 10-16-79

RECEIVED

OCT 21 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bob Davis TITLE Assist. Admin. Asst DATE 10-24-79

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE ACTING DISTRICT ENGINEER DATE OCT 17 1980
CONDITIONS OF APPROVAL, IF ANY:

0+4 USGS-H, 1-Hou, 1-Susp, 1-BD