

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-26070

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
Doyle Hartman

3. Address of Operator  
P. O. Box 10426, Midland, Texas 79702

4. Well Location  
Unit Letter J : 2250 Feet From The South Line and 1650 Feet From The East Line  
Section 31 Township 24-S Range 37-E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3224 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☒ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 10-30-89 RU John West Engineering. Found PBTD @ 3192' GL. 17' of fill. RD John West.  
11-1-89 Install American Size C57D-76-54 pumping unit.  
11-5-89 RU Clark Well Service. POOH w/95 jts 2-3/8" tbg + SN. Remove Cameron wellhead.  
Install Larkin 5-1/2 x 2-3/8" type MR tbghead.  
11-6-89 RU foam unit. Clean well out to PBTD of 3213' RKB. Ran 102 jts 2-3/8" tbg + SN + MA.  
Ran 3/4" API Class "C" rod string and 1-1/4" insert pump. Place well on pump.  
11-7-89/ Well tested pumping 22 BWPD (.92 BWPH) with gas unmeasured.  
11-12-89  
11-13-89 POOH w/tbg and rods. RU Capitan Perforators. Perforate well with additional 8 holes.  
1 SPF @ 2908, 2938, 2946, 2953, 2970, 2974, 2978.5 and 3016' RKB. Acidize well with  
3000 gals 15% NEFE on spot. Displace acid w/3000 gals 2% KCL water at rate of 1/3 BPM.  
11-14-89 Ran 101 jts 2-3/8" tbg + SN + MA. Landed tbg at 3172' RKB. SN @ 3154' RKB. Swab  
well to pit for 3 hours. Recover load water. Ran 126 - 3/4" API Class "C" rods with  
1-1/4" x 12" x 2" insert THD pump. Begin pumping well.

CONTINUED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Michael Stewart TITLE Engineer DATE 11-21-89

TYPE OR PRINT NAME Michael Stewart

TELEPHONE NO. 915/684-4011

(This space for State Use)

**ORIGINAL SIGNED BY JERRY SEXTON**  
**DISTRICT I SUPERVISOR**

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

**NOV 27 1989**

CONTINUED

11-15-89 Testing well

11-16-89 Evaluating results