

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR  
Amoco Production Company3. ADDRESS OF OPERATOR  
P.O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL X 660' FWL, Sec. 24  
AT TOP PROD. INTERVAL: (Unit L, NW $\frac{1}{4}$ , SW $\frac{1}{4}$ )  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

SEP 27 1979

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO5. LEASE  
NM-24490

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Andrikopoulos Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME  
Wildcat Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

24-25-33

12. COUNTY OR PARISH  
Lea13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3335.3 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to a TD of 5,000' and ran 10-3/4" 40 $\frac{1}{2}$ # casing set at 5,000'. Cemented with 3,500 sx Lite with additives and 200 sx Class C cement with 2% CACL. Plug down 11:50 PM 9-6-79. Circulated 375 sx. Wait on cement 24 hours. Tested casing with 1000# for 30 minutes. Test ok. Reduced hole to 9 $\frac{1}{2}$ " and resumed drilling.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Cox

TITLE Admin. Supervisor DATE 9-21-79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-H 1-Hou 1-Susp 1-BD 1-Yates

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

SEP 27 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO