

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O. C. G.

SUBMIT IN TRIPLICATE
(Other Instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

1. LEASE DESIGNATION AND SERIAL NO.

LC 060942

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Justis Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Langlie Mattix

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11, T25S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR

2100 First National Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface330' FSL & 2310' FEL Section 11, T-25-S, R-37-E,
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3129 GL (3139 RKB)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

ALTERING CASING

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Casing & Cementing

☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The well was spudded 1-12-80

Drilled 15" hole and set 30' of 11-3/4" - 33 Lb. Grade B Conductor Pipe and cemented with Redimix to surface.

Drilled 11" hole and set 432' of 8-5/8" 28 Lb. Grade B Surface Casing and cemented with 225 sx Class C 2% Cacl. Circulated 60 sx (Work accomplished 1-13-80)

Drilled 7-7/8" hole & set 3450' of 5 1/2" 17 Lb. J-55 Production Casing as follows:

Float Shoe	.50'
One Jt. 5 1/2"	40.20'
Float Collar	1.50'
85 Jts. 5 1/2"	3,407.80'
Total	3,450.00'

Cemented with 500 sx Class C 3% Econolite and 250 sx Class C 50-50 Pozmix.
Circulated 120 sx. (Work accomplished 1-22-80)

RECEIVED

JAN 25 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Tommy Whipple

TITLE Executive Vice President

DATE 1-23-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side