

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

3-NMOCC-HOBBS 1-BH, FIELD CLK
1-R. J. STARRAK-TULSA 1-BB, OFC TECH
1-A. B. CARY-MIDLAND 1-CK, FOREMAN
1-ELB, ENGR. 1-TEXACO, HOBBS
1-FILE 1-TEXACO, MIDLAND

SUNDRY NOTICES AND REPORTS ON LEASES

(DO NOT USE THIS FORM FOR NOTICES TO OIL OR GAS LEASES OR TO A DIFFERENT RESERVOIR.
USE THIS SECTION FOR REMEDIAL WORK (FORM C-101) FOR SUCH PURPOSES.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
Getty Oil Company

3. Address of Operator
P. O. Box 730, Hobbs, NM 88240

4. Location of Well
UNIT LETTER M 990 FEET FROM THE South LINE AND 990 FEET FROM
West LINE, SECTION 32 TOWNSHIP 24-S RANGE 38-E NMPH.

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

7. Unit Agreement Date

8. Form of Lease Name
Mexico "J"

9. Well No.
26

10. Field and Pool, or Wildcat
Dollarhide Fusselman

12. County
Lea

13. Elevation (Show whether DF, RT, GR, etc.)
3139' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPER. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOG ☒
OTHER ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-28-79 Reached TD 8750' at 4:30 p.m.

12-31-79 Drilled 7 7/8" hole to 8750'. Ran CNL-Density 8744' to surface; DLL-MSFL 8745 to 5000' and BHC Sonic 8740' to 5000'. Ran 200 jts. (8740') 5 1/2" csg. and set at 8746'. Halliburton cemented:
1st stage: 650 sxs Class "H" cement with .7% CFR-2, 18% salt, and 1/4# floccel/sx. Plug down at 1:30 p.m. 100 sxs cement circulated.
2nd stage: 1000 sxs Lite with .5% CFR-2, 18% salt, 1/4# floccel, 5# gilsonite/sx tailed in with 200 sxs Class "C" cement with .5% CFR-2 and 18% salt/sx. 75 sxs cement circulated. Plug down at 7:00 p.m. Total cement 1850 sxs. WOC.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 1-2-80

APPROVED BY _____ TITLE _____ DATE JAN 1 1980

CONDITIONS OF APPROVAL, IF ANY: