

P. O. BOX 1980
HOBBS, NEW MEXICO

NOTICE OF GAS CONNECTION

DATE 12/19/79

This is to notify the Oil Conservation Division that connection for the
purchase of gas from the Doyle Haritman

OPERATOR

Santa Federal #1

Lea Co.

M 27-25-37

LEASE & WELL

COUNTY

UNIT S-T-R

Jalmat

El Paso Natural Gas Company
NAME OF PURCHASER

POOL

was made on December 18, 1979

60664 -2

02

DATE

SITE CODE & SITE WELL NUMBER

El Paso Natural Gas Co.

PURCHASER

Francis L. Elliott
REPRESENTATIVE

Gas Production Status

TITLE

TRE: b1

cc: Operator

Oil Conservation Division - Santa Fe, NM

H. P. Logan

M. E. McEuen

R. L. Tabb

Proration Dept.

Measurement Dept.- Jal

Earl Smith

File

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032579-e

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Santa Fe Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Jalmat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 27, T-25-S

R-37-E, NMPM

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Doyle Hartman

3. ADDRESS OF OPERATOR

508 C & K Petroleum Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660 FSL and 660 FWL Section 27

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3012 G. L.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Cement and Set Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled well to a total depth of 3400'. Ran 93 joints (3402 feet) of 5 1/2 OD, 17 lb/ft, J-55, ST&C casing and landed casing at 3400 feet RKB with float shoe at 3400 feet. Cemented casing with 300 sx of API Class-C cement containing 3% gel and 1/4 lb/sx floreal followed by 250 sx of a 50-50 blend of API Class-C cement and Pozmix "A" containing 18% salt and 1/4 lb/sx floreal. Plug down at 4:00 AM CST 12-1-79. Circulated 75 sx of excess cement to pit. Pressure tested casing to 1500 psi. Pressure held okay.

RECEIVED

DEC 5 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Michelle HernandezTITLE Assistant Office ManagerDATE 12-03-79

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side