

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

|   |
|---|
| WELL API NO.<br><u>30-025-26595</u>   |
| 5. Indicate Type of Lease<br>STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil & Gas Lease No.  |
| 7. Lease Name or Unit Agreement Name<br>Bates BB&S  |
| 8. Well No.<br>1  |
| 9. Pool name or Wildcat<br>Jalmat (Tansill-Yates-7 Rivers)  |

|  |  |
|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS<br>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)           |  |
| 1. Type of Well:<br>OIL <input type="checkbox"/><br>WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER   |  |
| 2. Name of Operator<br>Meridian Oil Inc.   |  |
| 3. Address of Operator<br>P.O. Box 51810, Midland, TX 79710-1810   |  |
| 4. Well Location<br>Unit Letter <u>E</u> : <u>1870</u> Feet From The <u>North</u> Line and <u>280</u> Feet From The <u>West</u> Line<br>Section <u>29</u> Township <u>25-S</u> Range <u>37-E</u> NMPM Lea County |  |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.)<br><u>3024' RKB</u>   |  |

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Notify OCD prior to commencing plugging operations.

Set CIBP on tbg @ +/-2650'.

Spot cement plug on top of CIBP @ 2475' to 2650' (20 sxs). Plug will cover base of salt section.

Circ hole w/ 9 ppg gelled brine. Spot a cement plug across the top of the salt @ 1110' - 1230' (15 sxs). Use Class C cement w/ 2% CaCl<sub>2</sub>.

Spot a plug across surface of casing shoe @ 600' - 705' (15 sxs). Use Class C cement w/ 2% CaCl<sub>2</sub>. Pull up to 50' and circ cement to surface (5 sxs).

Cut off casing 3' below ground level and install dry hole marker. Clear and restore location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roxann Scholz TITLE Production Asst DATE 04/09/92

TYPE OR PRINT NAME Roxann Scholz

TELEPHONE NO. (915)688-6943

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: