

**COPY TO O. C. C.**  
**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY**

SUBMIT IN TRIPlicate\*  
(Other instructions  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 0325 11 (e)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Ruby Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Jalmat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8, T-25-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

1.

OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR

Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR

2100 First National Bank Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)  
At surface

1880' FEL & 660' FSL Section 8, T-25-S, R-37-E,  
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3152 G.L. (3162 RKB)

16.

Check Appropriate Box To Indicate Nature of Well, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF   
 FRACTURE TREAT   
 SHOOT OR ACIDIZE   
 REPAIR WELL   
 (Other)

PULL OR ALTER CASING   
 MULTIPLE COMPLETE   
 ABANDON\*   
 CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF   
 FRACTURE TREATMENT   
 SHOOTING OR ACIDIZING   
 (Other) Casing & Cementing

REPAIRING WELL   
 ALTERING CASING   
 ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The well was spudded 2-5-80

Drilled 15" hole and set 30' of 12-3/4" - 30 Lb. Grade B Conductor Pipe and cemented with Redimix to surface.

Drilled 12 1/4" hole and set 406' of 8-5/8" 28 Lb. Grade B Surface Casing and Cemented with 325 sx Class C 2% Cacl. Circulated 100 sx (work accomplished 2-6-80).

Oral permission from Jerry Long to reduce 8-5/8" surface pipe setting depth to 400'.

Drilled 7-7/8" hole & set 3300' of 5 1/2" 17 Lb. J-55 Production Casing as follows:

Guide Shoe	.50
One Jt. 5 1/2"	42.86
Float Collar	1.50
79 Jts. 5 1/2"	3,255.14
	<u>3,300.00</u>

Cemented with 350 sx Class C 3% Econolite and 250 sx Class C 50-50 Pozmix. Circulated 80 sx. (Work accomplished 2-13-80).

18. I hereby certify that the foregoing is true and correct

SIGNED

Tommy Phipps

TITLE Executive Vice President

DATE 2-19-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side