

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	F2XX1015G			X
AB	General Purpose "U" bolt clamp	UC51024GP			
BC	Lightening arrester, 10 KV				
CD	Single phase oil switch, 14.4 KV			W224W EDISON KWHC2	
DE	split bolt connector, size req'd			BLACKBURN W31015	
EF	grounding spec. see dep No. ES-11 & ES-1A, Note 3				
FG	35' class 4 creosoted pine pole				
GH	Aluminum deadend Piforma for ACSR, size req'd				
HI	30' class 6 creosoted pine pole				
IJ	OVERHEAD GRND, #4 ACSR - If Req'd - Ref. Dep ES-11,				
JK	FS-1A - Note 3				
LL	Ground connector, motor				
MM	600 V. secondary lightning arrester single phase				
NN	Greenfield Type EF liquid-tight flexible steel				
OO	conduct, size req'd, w/ necessary liquid-tight				
PP	connectors.				
QQ	req'd size 1/2 fitting & cover & gasket				
RR	strain former, rank grounding, central	GW3-75			
SS	Bird Guards (insulating boots on transformer bushings)			W224W EDISON KWHC2	

DATE: 12-27-71	TITLE: DESCRIPTION MATERIAL
DRAWN BY: E. WINTER	
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	
JOB: PRODUCTION DEPT. CONOCO HOBBS DIVISION DRAWING NO: ES-1 SHEET 2 OF 3	