

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt s/aq. nut, round washer, and center key on short end, sq. nut and WF locknut on long end, 13 1/8" long (for length required.)	7828			
b	wet process porcelain secondary spool insulator, 3" brown glaze		4101		
d	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. DWG ES-18 Note: provide clamp and ground conduit parallel groove clamp, size req'd			BURNDY 54442 "UC"	
e	secondary insulator clevis for 4" insulator	6510			
f	5/8" thimble nut				
h	5/8" x 12" (or length req'd) straight thimble bolt w/aq. nut	5512		ALUMINUM 6M3-6	X
j	transformer cluster mount bracket (small)			ALUMINUM 15M3-6	X
l	transformer cluster mount bracket (large)				
m	req'd size valenlight disconnect & fuses, 3-phase, 600 V. Ref. DWG NG ES-18				
n	16" cross plate anchor (or size req'd)	X-16			
q	8-way expanding anchor (size req'd)	88135			
t	4" brown glaze wet process porcelain secondary spool insulator		10101		
u	5/8" x 3' thimble anchor rod w/nut (use twineye if req'd - Chance No. 5342)	5317 (NUT 55006P)			
ae	3/8" high strength guy, 3/8" (10,000 lb.)				
bb	performed guy grip for 3/8" guy strand	5010			
dd	3/8" x 10" angle thimble bolt w/nut	6823 1/2			X
ee	3" x 3" x 1/4" x 11/16" hole curved washer				
ff	6" - guy clamp w/3-1/2" bolts				
gg	medium size strain insulator	6454			
hh	serving sleeve for 3/8" guy strand	7887			X
jj	3/16" x 2-1/2" x 7" lift plate				
nn	pole bottom ground plate (may use butt-wrap if desired)				
qq	Ground connection (See DWG. ES-18)				
rr	wet process porcelain secondary spool insulator, 3" - white glaze				
tt	wet process porcelain secondary spool insulator, 4" - white glaze				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPMS	DRAWING NO: ES-1
		SHEET 50 OF 5	