

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-83

API NO. 30-025-26676

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Phillips Petroleum Company	5. State Oil & Gas Lease No. -----
3. Address of Operator Room 401, 4001 Penbrook Street, Odessa, Texas 79762	7. Unit Agreement Name -----
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>10</u> TOWNSHIP <u>25-S</u> RANGE <u>36-E</u> N.M.P.M.	8. Farm or Lease Name Meador-A
	9. Well No. 1
	10. Field and Pool, or Wildcat (Undesignated) Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3165.6' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-11-80 MI Cactus Drilling

4-12-80 Spud in w/17-1/2" bit - Drld to 465'

4-17-80 Ran 42 jts 13-3/8" 61# & 68# K-55 csg. Set at 1644'.

4-18-80 Cmt w/925 sxs Cl. "H" w/10% DD, 2% CaCl₂, 1/4#/sx Celloflake, 2% Defoam.. Tail w/350 sxs Cl. "H" w/2% CaCl₂, 2% Defoam. Circ 70 sxs to surface. WOC 20-1/2 hours. Tested BOP and csg. to 2500#. OK Went in hole w/12-1/4" bit. Drlg. ahead.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller TITLE Senior Engineering Specialist DATE May 12, 1980

Orig. Signed by Jerry Sexton

APPROVED BY Dist 1, Supv. DATE MAY 12, 1980

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 16 1980

OIL CONSERVATION DIV.

RECEIVED

MAY 13 1980

G. C. D.
ARTESIA, OFFICE