

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLY
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 060942

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Justis Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Langlie Mattix

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11, T25S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR

2100 First National Bank Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface330' FSL & 660' FEL Section 11, T-25-S, R-37-E,
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3118 GL (3128 RKB)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Casing & Cementing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

The well was spudded 3-3-80

Drilled 15" hole and set 30' of 12-3/4" - 33 Lb. Grade B Conductor Pipe
and cemented with Redimix to surface.Drilled 12 1/4" hole and set 438' of 8-5/8" 28 Lb. Grade B Surface Casing
and cemented with 300 sx Class C 2% Cacl. Circulated 75 sx (Work
accomplished 3-4-80)Drilled 7-7/8" hole & set 3450' of 5 1/2" 17 Lb. J-55 Production Casing
as follows:

Float Shoe	.50'
One Jt. 5 1/2"	43.30
Float Collar	1.50'
85 Jts. 5 1/2"	3,404.70
Total	3,450.00'

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICOCemented with 300 sx Class C 3% Econolite and 250 sx Class C 50-50 Pozmix.
Circulated 63 sx. (Work accomplished 3-11-80)

18. I hereby certify that the foregoing is true and correct

SIGNED

Tommy Phipps

TITLE

Executive Vice President

DATE

3-14-80

(This space for Federal or State office use)

RECEIVED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAR 25 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side