

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 032579 (f)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Beverly Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Jalmat (Gas)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 27, T25S, R37E,
NMPM

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Alpha Twenty-One Production Company		8. FARM OR LEASE NAME El Paso Beverly Federal	
3. ADDRESS OF OPERATOR 2100 First National Bank Building, Midland, Texas 79701		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL, 660' FWL, Section 27, T25S, R37E, Lea County, New Mexico		10. FIELD AND POOL, OR WILDCAT Jalmat (Gas)	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3028 G.L. (3038 RKB)	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T25S, R37E, NMPM	
		12. COUNTY OR PARISH Lea	
		13. STATE N. M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing & Cementing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The well was spudded 4-7-80

Drilled 15" hole and set 30' of 12-3/4" - 30 Lb. Grade B Conductor Pipe and cemented with Redimix to surface.

Drilled 12 1/4" hole and set 453' of 8-5/8" 28 Lb. Grade B Surface Casing and cemented with 300 sx Class C 2% Cacl. Circulated 25 sx. (Work accomplished 4-8-80)

Drilled 7-7/8" hole and set 3,300' of 5 1/2" 17 Lb. J-55 Production Casing as follows:

Guide Shoe	.50
1 Jt. 5 1/2" Casing	43.14
Float Collar	1.50
87 Jts. 5 1/2" Casing	3,254.86
	3,300.00

Cemented with 300 sx Econolite w/1/4 Flocele, 5 Lb. Gilsonite

300 sx Class C 50-50 Pozmix, w/1/4 Flocele & 9 Lb. Salt.

Circulated 85 sx. (Work accomplished 4-14-80)

RECEIVED

APR 16 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Executive Vice President

DATE

4-15-80

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

K. E. Saylor
APR 28 1980U. S. GEOLOGICAL SURVEY
LOS WELLS, NEW MEXICO

*See Instructions on Reverse Side