

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

88245 BASE

LC 054667

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Tom Federal No. 2

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Langlie Mattix SRQ

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22, T-25-S, R-37-E

12. COUNTY OR PARISH

13. STATE

Lea

New Mexico

14. API NO.

30-025-26725

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3000.5' GL

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR

P.O. Box 1206, Jal, NM 88252

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650' FNL & 330' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

(Work commenced on 5-20-85)

Perforated 19 shots (.43 diameter) from 3182' to 3274' as follows:  
3182', 3183', 3185', 3195', 3198', 3199', 3210', 3216', 3217', 3218',  
3226', 3227', 3259', 3260', 3266', 3267', 3272', 3273', 3274'.

Hydrotested tubing to 5000 psi and acidized with 3000 gals 15%. Had good ball off. Opened well up for flowback. Had good show of gas and slight show of oil. Put well on production.

Well down to replace split joints of tubing.

(Work completed 6-3-85)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R.W. Lansford

TITLE VP/Energy Resources

DATE July 1, 1985

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUL 5 1985

\*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO

100-443887-1000

JUL -9 1985

100-443889-1