

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 19859
2. NAME OF OPERATOR HNG Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 2267, Midland, Texas 79702		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL & 660' FNL, Sec. 11		8. FARM OR LEASE NAME Bell Lake "11" Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3408' GR		10. FIELD AND POOL, OR WILDCAT Wildcat (Morrow)
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 11, T25S, R33E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

## 18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF: 4-16-80

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other) casing test &amp; cement job

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-5-80 Set 12,934' of 7"  
4207' 26# P-110 TS  
5437' 26# P-110 LT&C  
3290' 26# S-95 LT&C

Cemented with 500 sx HLW w/5# KCL & .6 of 1% Halad 22 mixed at 12.7 ppg and 500 sx C1 H w/3#/sx KCL .4 of 1% CFR-2 and .6 of 1% Halad 22 mixed at 16.4 ppg. Pressure tested to 2000# WOC 24 hours.

RECEIVED

MAY 9 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Betty Gildon Betty GildonTITLE Regulatory ClerkDATE May 8, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

ACCEPTED FOR RECORD

DATE

MAY 20 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side