

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on  
verse side)

COPY TO O. C. G.

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

|  |   |
|--|---|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER  | 5. LEASE DESIGNATION AND SERIAL NO.<br>NM 19859                         |
| 2. NAME OF OPERATOR<br>HNG Oil Company   | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME                                    |
| 3. ADDRESS OF OPERATOR<br>P.O. Box 2267 Midland, Texas 79702   | 7. UNIT AGREEMENT NAME  |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*<br>See also space 17 below.)<br>At surface<br><br>1980' FEL & 660' FNL, Sec. 11 | 8. FARM OR LEASE NAME<br>Bell Lake 11 Federal                           |
|  | 9. WELL NO.<br>1  |
|  | 10. FIELD AND POOL, OR WILDCAT<br>Wildcat (Morrow)                      |
|  | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA<br>Sec. 11, T25S, R33E |
| 14. PERMIT NO.<br>approved 3-5-80  | 12. COUNTY OR PARISH<br>Lea   |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.)<br>3408' GR   | 13. STATE<br>NM   |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF: 2-4-80

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON\* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT\* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) CSG. test & cement job ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-4-80 Spud 4:15 p.m.

4-5-80 Set 578' of 13-3/8" 48# H-40 ST&C. Circulated Cemented w/250 sx HLW W/2% CaCl & 1/2#/sx flocele mixed at 12.7 ppg and 250 sx ClC w/2% CaCl mixed at 14.8 ppg. Pressure tested to 500 psi. WOC 20 hours.

RECEIVED

APR 16 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Betty A. Gildon TITLE Regulatory Clerk

DATE 4-15-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

ACCEPTED FOR RECORD

DATE

APR 25 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side