

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other Instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 054667

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Alpha Twenty-One Production Company		8. FARM OR LEASE NAME El Paso Tom Federal	
3. ADDRESS OF OPERATOR 2100 First National Bank Building, Midland, Texas 79701		9. WELL NO. 3	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310 FNL, 1650 FWL, Sec. 33, T25S, R37E Lea County, New Mexico		10. FIELD AND POOL, OR WILDCAT Langlie Mattix	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T25S, R37E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2999 G.L. (3009 RKB)		12. COUNTY OR PARISH Lea	
		13. STATE NM	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Casing &amp; Cementing

☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The well was spudded 9-2-80.

Drilled 15" hole and set 30' of 12-3/4" - 33 Lb. Grade B Conductor Pipe, and Cemented with Redimix to Surface.

Drilled 12 1/4" hole and set 446' of 8-5/8" 28 Lb. Grade B Surface Casing, and Cemented with 300 Sx. Class C 2% Cacl. Circulated 100 Sx.

(Work accomplished 9-3-80).

Drilled 7-7/8" hole &amp; set 3300' of 5 1/2" 17 Lb. J-55 Production Casing as follows:

Float Shoe	.80'
One Jt. 5 1/2"	40.00'
Float Collar	1.50'
83 Jts. 5 1/2"	3,257.70'

Total	3,300.00
-------	----------

RECEIVED

SEP 12 1980

U. S. GEOLOGICAL SURVEY  
HOBBES, NEW MEXICO

Cemented with 350 Sx. Class C 3% Econolite and 250 Sx. Class C 50-50 Pozmix. Circulated 15 Sx. (Work accomplished 9-10-80).

18. I hereby certify that the foregoing is true and correct

SIGNED

Tommy Phillips

TITLE Executive Vice President

DATE 9-10-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

SEP 18 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side