

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 054667

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso Tom Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Langlie Mattix

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 33, T25S, R37E

12. COUNTY OR PARISH 13. STATE

Lea

N.M.

1. OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR

2100 First National Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1650 FSL, 1650 FWL, Sec. 33, T25S, R37E
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2991 G.L. (3001 RKB)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Casing & Cementing ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The well was spudded 9-10-80.

Drilled 15" hole and set 30' of 12-3/4" - 33 Lb. Grade B Conductor Pipe,
and Cemented with Redimix to surface.

Drilled 12 1/4" hole and set 434' of 8-5/8" 28 Lb. Grade B Surface Casing,
and Cemented with 300 Sx. Class C 2% Cacl. Circulated 80 Sx.

(Work accomplished 9-11-80).

Drilled 7-7/8" hole & set 3300' of 5 1/2" 17 Lb. J-55 Production Casing
as follows:

Float Shoe

1.80'

One Jt. 5 1/2"

40.03'

Float Collar

1.60'

82 Jts. 5 1/2"

3,256.57'

Total

3,300.00'

RECEIVED

SEP 22 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Cemented with 300 Sx. Class C 3% Econolite and 300 Sx. Class C 50-50 Pozmix.
Circulated 14 Sx. (Work accomplished 9-17-80).

18. I hereby certify that the foregoing is true and correct

SIGNED

Tommy Phipps

TITLE Executive Vice President

DATE 9-18-80

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF

ACCEPTED FOR RECORD

APPROVAL, IF ANY:

SEP 23 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

TITLE

DATE

*See Instructions on Reverse Side