

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Gifford, Mitchell & Wisenbaker

3. ADDRESS OF OPERATOR

1280 MNB Tower, Midland, Texas 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FWL & 1880' FNL of Sec. 7

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐☒

RECEIVED

JUL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY
HOUSTON, TEXAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-23-81 Tbg. to 3522' - 25 sxs. cement (top 3335).

4-24-81 Fill hole with mud. Shot 5½ at 2375'. Rec. 56 fts.

4-25-81 Tbg. to 2425'. Spot 50 sxs. cement (top cement 2310')

Tbg. to 1780'. Spot 50 sxs. cement

Tbg. to 1414'. Spot 50 sxs. cement (top cement 1290')

4-27-81 Set 10 sxs. cement at top of hole, weld plate on 8-5/8" and set dry hole marker.

LOCATION READY FOR INSPECTION

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

L. B. StiffTITLE Prod. ManagerDATE June 12, 1981APPROVED BY
CONDITIONS OF APPROVAL(Orig. Seal) PETER W. CHESTER

TITLE

DATE

JUL 21 1981

FOR

JAMES A. OLLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side