	COP	ΥT	0	0.	С.	С
--	-----	----	---	----	----	---

1

Form 9–331 Dec. 1973	Form Approved. Budget Bureau No. 42-R1424					
UNITED STATES	5. LEASE	Budget	Bureau N	o. 42-R142	4	
DEPARTMENT OF THE INTERIOR		34481				
GEOLOGICAL SURVEY		ALLOTTEE (		NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGE	REEMENT NA	ME			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		esignated LEASE NAME		<u>51.6</u> 113.5		
		e Mountai	- ,	eral		
well well other	9. WELL NO		<u></u>	55. 55.		
2. NAME OF OPERATOR Gifford, Mitchell & Wisenbaker	1		5		- <sup>1</sup> .	
3. ADDRESS OF OPERATOR	10. FIELD OR	dcat 3	ME: E	Nffi Dirib Latin		
1280 Midland Nat'l Bank Twr. Midland, Tx 7970	11. SEC., T.,					
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	2 8 8 8 2 8 2 8 8 8 8 8 8 8 8 8 8 8 8 8	non Non	522	/	
below.) AT SURFACE: 660' FWL & 1880' FNL of Sec. 7		<u>c_7, ₹1-</u> 2	25 <u></u> S, 7	R-36-E		
AT TOP PROD. INTERVAL:	12. COUNTY		13 STA			
AT TOTAL DEPTH:	Lea 14. API NO.	<u>- 930511</u>	lew Me	X1.CO		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			lead			
REPORT, OR OTHER DATA	15. ELEVATIO	INS (SHOW I			)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	332	1GR 2	6 5	<u>වේ</u> ය වි මේ ම	-,	
TEST WATER SHUT-OFF		0 2 3 3 0 2 3 3	20	bo bo		
		e sa to	- siol	ido: Vii b	5	
SHOOT OR ACIDIZE	<b></b> - *	17 50 3117 40 5	ond:			
PULL OR ALTER CASING		e on Form 9-23		brithe all zo		
MULTIPLE COMPLETE			EU		Ű	
CHANGE ZONES					ST INT	
(other)	i i i i i i i i i i i i i i i i i i i	53338 CC234	a " 3	14 ) 🖉 🚊	SURVEY	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	e all pertinent o	etails; and e		Bentite ate	s,	
measured and true vertical depths for all markers and zones pertiner	it to this work.)*	r Sive subsi	11130000	cations ar	nd	
			10,			
8/8/80 - ran 8 5/8" 24# casing and set at 1414	with	H G H J G	4 pÅ	ី ភី ភី ខ្ម ខ្ម		
475  sx HLW  w/2% CaCl mixed at 12.2 pp		topar horman conversional conve	clions. Siste requirements, locatio over below or will be leaded	g of alsead Bulations, r Subtions, r		
by 300 sx Class C cement w/2% CaCl mix			<u>)</u> ਦ 			
ppg. Cement circulated. WOC 18 hours		9 00 00 2 00 00 2 00 00 2 00 00	ent. Ente			
casing at 500 psi – Held OK.		101 101 101 101 101 101 101 101 101 101	uêur Ph. M			
			inh 386.0		ى تارىغا تاۋىلىيە <b>مۇ</b> را تاۋا	
			actore Sectoredu powe pajow			
			ad anvedu u No Schola A			
		9 1 2 2 2 2 7 2 2 2 5 2 2		말했던		
			ਤੇ ਹੁੰਦ	200 gr Gr 20 A		
Subsurface Safety Valve: Manu. and Type		Set @			Ft.	
18. I hereby certify that the foregoing is true and correct				े दे स्टार अन्य म		
$() V = \frac{1}{2} \frac{1}{$			원을 수 성용 신			
SIGNED SIGNED TITLE Prod_ Engine	er date	<u>    8/11/80</u>	<u>é en é</u>	9 <u>28</u> 281		
(This space for Federal or State off	ice use}	ACCEPT	ו פרש נו	HCOPD	=	
APPROVED BY TITLE	DATE	ACCEPTI				
CONDITIONS OF APPROVAL, IF ANY:			10	Č		
		ÂU	G 1 41	980		
		に言語に		ŝź.		
*See Instructions on Reverse	Side	U.S. GEO				
		I ROSWEL	l, new	MEXICO		