

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRII
(Other instruction
verse side)

ATE*
n re

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-052956

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso-Wells Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Jalmat (Gas)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 4, T-25-S,
R-37-E, NMPM

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Doyle Hartman

3. ADDRESS OF OPERATOR

P. O. Box 10426, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980 FNL & 660 FWL (E)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3220 G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud Notice and Set Surface

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well at 7:00 p.m. 8-25-80. Drilled well to a total depth of 434' RKB. Ran 11 joints (435') of 8 5/8 OD, 24 lb/ft, H-40, ST&C casing and landed at 431' RKB. Cemented casing with 150 sx of API Class C cement containing 4% gel and 1/4 lb/sx floreal followed by 150 sx of API Class C cement containing 2% CaCl and 1/4 lb/sx floreal. Plug down at 7:30 a.m. 8-26-80. Circulated 120 sx of excess cement to pit. WOC 18 hours. Pressure tested casing to 700 psi. Pressure held okay.

RECEIVED

AUG 29 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Michelle Hernandez TITLE Administrative Assistant

DATE August 27, 1980

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

SEP 5 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side