M. M. CIL CONS. COMMISSION

P. O. BUIL 1930

Form 9-331 Dec. 1973

1

HODDS, NEW MEXICO 88240

Form Approved. Budget Bureau No. 42-R1424

NM

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

5. LEASE NM-24490

9. WELL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME Andrikopolous

SUNDRY NO	TICES AND	REPORTS	ON	WELLS
-----------	-----------	---------	----	-------

(Do not use this form for proposals to drill or to deepen or plug back to a different

reservoir. Use Form 9-331-C for such proposals.)											
1.	oil well	X	ga we	s III		other					
2.	NAM					ion Co	mnanı	,			
		AIIIC	100	FIUC	iuci	TON CO	whan	<u> </u>			
3.	ADDF	RESS	OF C	PER	ATOR						
		Р.	0. 1	Box	68,	Hobbs	, NM	88240			
4.	LOCA	TION	OF \	NELL	(REF	PORT LO	CATION	CLEARLY.	See	space	17

10. FIELD OR WILDCAT NAME Wildcat Delaware 11. SEC., T., R., M., OR BLK. AND SURVEY OR

below.) 1980' FSLx 1980' FWL, Sec. 27 AT SURFACE: (Unit K, NE/4, SW/4) AT TOP PROD. INTERVAL:

24-25-33 12. COUNTY OR PARISH 13. STATE

AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

14. API NO. 30-025-27124

15. ELEVATIONS (SHOW DF, KDB, AND WD) 3332.4 GL

SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 4-29-82 (Tyler 105). Pulled tubing, rods, and pump. Ran cement retainer set at 5093'. Squeezed with 100 sacks-class C neat cement. Spotted a 25 sack plug on retainer. Spotted a 21 sack plug from 1250'-1050'. Spotted a 21 sack plug from 700'-500'. Spotted a 15 5 5 ack surface plug. Erected PxA marker and moved out service unit

0+6- USGS,R 1- HOU 1- DMF 1- Stafford, Hou

Subsurface Safety Valve: Manu. and Type _

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ast. Adm. Analyst

5-17-82

_ DATE

(This space for Federal or State office use)

APPROVED B CONDITIONS OF APPROVAL, IF ANY:

7 1982

DISTRICT SUPER ASOL

*See instructions on Reverse Side