

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

N. M. OIL & GAS COMMISSION  
P. O. BOX 1080  
HOBBS, NEW MEXICO 88240

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐  
2. NAME OF OPERATOR ARCO Oil and Gas Co.  
Division of Atlantic Richfield Co.  
3. ADDRESS OF OPERATOR  
P. O. Box 1710, Hobbs, N M 88241-1710  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FSL & 660' FEL (Unit Ltr I)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: As above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

(other)

Spud, run surface csg & cmt.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
J. H. McClure "B"

9. WELL NO.  
22

10. FIELD OR WILDCAT NAME  
Dellarhide Tubb Drinkard

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
19-24S-38E

12. COUNTY OR PARISH 13, STATE  
Lea N M


14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3175.8' CR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud 18" hole on 10/15/81. Drld to 30'. RIH w/31' of 14" conductor pipe, set @ 30'. Cmtd w/2 yd Redi-mix to surf. Spudded 12 1/4" hole @ 3:00 PM, 10/16/81. Fin drlg 12 1/4" hole to 1293' @ 3:00 PM, 10/17/81. RIH w/8-5/8" OD 24# K-55 csg set @ 1293'. Cmtd 8-5/8" OD csg w/600 sx Cl C cmt contg 4% gel, 1/2#/sk flocele followed by 250 sx Cl C cmt contg 2% CaCl<sub>2</sub>. Circ 150 sx cmt to surf. PD @ 11:50 PM, 10/17/81. WOC 48 hrs. Press tsld csg to 1000# for 30 mins, OK. Drlg new fm w/7-7/8" bit @ 10:45 PM, 10/19/81.



Subsurface Safety Valve: Manul. and Type

U.S. GEOLOGICAL SURVEY  
ROSWELL NEW MEXICO

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED: A. CHAPMAN TITLE: Dist. Drlg. Supt. DATE: 10/21/81

(This space for Federal or State office use)

APPROVED BY: OCT 20 1981  
CONDITIONS OF APPROVAL

TITLE DATE

U.S. GEOLOGICAL SURVEY