

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N. M. OIL CONS. COMMISSION
P. O. BOX 1206
ROSBURG, NEW MEXICO 88240

Form approved
Budget Bureau No. 42-R1424
LEASE DESIGNATION AND SERIAL NO.
LM 40078

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. SITE AGREEMENT NAME
2. NAME OF OPERATOR Alpha Twenty-One Production Company		8. FARM OR LEASE NAME Buckskin Federal
3. ADDRESS OF OPERATOR P.O. Box 1206, Jal, NM 88252		9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2310 FEE and 330 PSI, Section 18, T-24-S, R-38-E		10. FIELD AND POOL, OR WILDCAT Fullerhide-Pubbs Drinkard
14. PERMIT NO.		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA S-1. 18, T-24-S, R-38-E
15. ELEVATIONS (Show whether RF, RT, GR, etc.) 3180' Ground Level		12. COUNTY OR PARISH BKA
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRAC TURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

WATER SHUT-OFF	REPAIRING WELL
FRAC TURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Casing & Cementing	XXX

NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)


The well was spudded 6-16-82

Drilled 15" hole and set 30' of 12-3/4" Grade B Conductor Pipe and cemented with Redimix to surface.

Drilled 12-1/2" hole and set 1263.29' of 8-5/8" 24#, Grade I Surface Casing and cemented with 700 sx Class "C", CAC12. Circulated 225 sx. Work accomplished 6-19-82)

Drilled 7-7/8" hole and set 6811.49' of 5-1/2" 17#, K-55 Production Casing as follows:

Floater shoe	1.65'
Shoe jt.	20.03'
Floater Collar	1.55'
66 jts.	2677.23'
EV Tool	3.10'
101 jts.	4107.93'
Total	6811.49'



Cemented in Two Stages:

First Stage: 975 sx 50/50 Pozmix. Circulated 200 sx.

Second Stage: 1435 sx Halliburton Lite and 200 sx Class "C". Circulated 300 sx.
(Work accomplished 7-1-82)

18. I hereby certify that the foregoing is true and correct.

SIGNED

Robert W. Lunsford
ROBERT W. LUNSFORD

TITLE V.E./Energy Resources

DATE 7-7-82

(This space for Federal or State official use only.)

APPROVED BY

Robert W. Lunsford
ROBERT W. LUNSFORD

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY:

OCT 7 1982

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side
ROSWELL, NEW MEXICO