

UNION STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLA E\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-063261

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-----

7. UNIT AGREEMENT NAME

-----

8. FARM OR LEASE NAME

Terra Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Langlie-Mattix

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 22-T25S-R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether depth, GR, etc.)

3087' GR

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒  
☐  
☐

REPAIRING WELL

☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7-7/8" hole to TD 3470'. Ran 95 jts. 5-1/2" 17# K-55 casing and cemented @ 3470' w/860 sx. Halliburton Lite cement containing 1/4#/sx. Flocele & 200 sx. 50-50 Pozmix containing 2% gel, 1/4#/sx Flocele, & 2% CaCl<sub>2</sub>. Plug down @ 8:45 AM 23 Feb., 1981. Did not circulate. After 6 hrs. WOC ran temp. survey - top cement @ 1600'. Released rotary rig.

Will perforate 5-1/2" casing and cement from 1600' to surface and test casing prior to completion operations.

18. I hereby certify that the foregoing is true and correct

SIGNED

*R. M. Williams*

TITLE Agent

DATE 24 February, 1981

(This space for Federal or State office use)

ACCEPTED FOR RECORD  
PETER W. CHESTER

APPROVED BY

CONDITIONS OF APPROVAL  
FEB 25 1981

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYCOPY  
SUBMIT IN TRI  
(Other, instructio  
verse side)DATE  
ON REForm approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC - 063261

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Terra-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Langlie-Mattix

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 22-T25S-R37E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

MORRIS R. ANTWEIL

3. ADDRESS OF OPERATOR

Box 2010, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL &amp; 2310' FWL Section 22

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3087' GR

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 7:30 AM 14 Feb., 1981.

Drilled 12-1/4" hole to 400'.

Ran 10 jts 8-5/8" 24# casing and cemented @ 400' w/250 sx. Class "C" cement containing 2% CaCl<sub>2</sub>.

Plug down @ 5:00 PM 14 February, 1981. Circulated 10 sx.

WOC 18 hrs. Tested casing w/2000 psi - 30 mins. - OK.

Drilled out and drilling ahead w/7-7/8" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED

*P. W. Chester*

TITLE

Agent

DATE 16 February, 1981

(This space for Federal or State and Local RECORD)

PETER W. CHESTER

TITLE

DATE

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

FEB 18 1981

U.S. GEOLOGICAL SURVEY  
ROSEMBO, NEW MEXICO

\*See Instructions on Reverse Side