

UNITED STATES OIL CONS. COM.
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
HOBBBS, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR ARCO Oil and Gas Company
Division of Atlantic Richfield Co.
3. ADDRESS OF OPERATOR
P. O. Box 1710, Hobbs, N M 88241-1710
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 660' FEL
AT TOP PROD. INTERVAL: as above
AT TOTAL DEPTH: as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF

- ☐
☐
☒
☐
☐
☐
☐
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

(other) Complete as single Oilwell

5. LEASE
LC-034117(a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
R. S. Crosby "A"
9. WELL NO.
4
10. FIELD OR WILDCAT NAME
Langlie Mattix 7R Qn
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
29-25S-37E
12. COUNTY OR PARISH Lea 13. STATE N M
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3024 5' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 7/09/81 drld out DV tool @ 2642' & FC @ 3357'. Pressure tested 5½" OD csg to 1500# for 30 mins, OK. Ran GR Corr log. Perf'd 7R Qn @ 3254, 60, 65, 71, 79, 85, 94' w/7-.41" holes. Acidized perfs 3254-94' w/2100 gals 15% NE-FE, flushed w/21 bbls 2% KCL wtr, ISIP 200#. In 5 hrs flwd 8 BO, 43 BW. Well died. In 7 hrs swbd 15 BO, 17 BW. POH w/trtg pkr. RIH w/2-3/8" OD tbg, set SN @ 3300'. Ran rods & pump. On 24 hr test 8/13/81 pmpd 28 BO, 10 BW, 33 MCFG, GOR 1179:1. On 24 hr potential test 8/17/81 pmpd 14 BO, 17 BW, 31 MCFG, GOR 2214:1.

FINAL REPORT.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James W. Schmidt TITLE Dist. Drlg. Supt. DATE 8/18/81APPROVED BY
CONDITIONS OFACCEPTED FOR RECORD
ROGER A. CHAPMAN

TITLE

DATE

AUG 24 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

ACCEPTED FOR RECORD

AUG 24 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO