

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 4355

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Justis Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Justis Glorieta

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 11, T25S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER JUN 9

2. NAME OF OPERATOR
Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR
2100 First National Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FNL and 990' FEL Section 11, T25S, R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3153 G. L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

| | | | |
|---------------------|--------------------------|----------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | PULL OR ALTER CASING | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | MULTIPLE COMPLETE | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | ABANDON* | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | CHANGE PLANS | <input type="checkbox"/> |
| (Other) | | | |

SUBSEQUENT REPORT OF:

| | | | |
|----------------------------|--------------------------|-----------------|-------------------------------------|
| WATER SHUT-OFF | <input type="checkbox"/> | REPAIRING WELL | <input type="checkbox"/> |
| FRACTURE TREATMENT | <input type="checkbox"/> | ALTERING CASING | <input type="checkbox"/> |
| SHOOTING OR ACIDIZING | <input type="checkbox"/> | ABANDONMENT* | <input type="checkbox"/> |
| (Other) Casing & Cementing | | | <input checked="" type="checkbox"/> |

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The well was Spudded 6-4-81.

Drilled 15" Hole and set 30' of 12-3/4" Conductor Pipe and Cemented with Redimix to Surface.
Drilled 12 1/4" Hole and Set 432' of 8-5/8" 28 Lb. Grade B Surface Casing and cemented with
300 Sx. Class C w/2% Cacl. Circulated 90 Sx. (Work Accomplished 6-5-81)
Drilled 7-7/8" Hole and Set 4,998' of 5 1/2" 15.5 Lb. J-55 Production Casing as follows:

| | |
|-----------------------|-----------|
| Guide Shoe | 1.65' |
| One Jt. 5 1/2" Casing | 39.98' |
| Float Collar | 1.50' |
| 49 Jts. 5 1/2" Casing | 1,953.25' |
| DV Tool | 3.05' |
| 75 Jts. 5 1/2" Casing | 2,998.57' |
| | 4,998.00' |

Cemented in Two Stages:

First Stage: 575 Sx. 50-50 Pozmix 2% Gel .2 Halite 4, 6 Lbs. Nacl.

Second Stage: 775 Sx. Halliburton Lite, 15 Lb. Nacl, 5 Lb. Gilsonite, 1/4 Lb. Flocele.
Circulated 250 Sx. (Work Accomplished 6-18-81)

18. I hereby certify that the foregoing is true and correct

SIGNED

Tommy Phillips

TITLE Executive Vice President

DATE 6-19-81

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY ROGER A. CHAPMAN

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 25 1981

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO